

Refrigerated Pastry Cabinet - H-P081VE6325



H-P081VE6325*

Technical parameters:

Model	Dimensions (ext.) H x W x D [mm]	Display surface [m ²]	Weight [kg]
H-P081VE6325 100	1367 x 1025 x 850	1,65	180
H-P081VE6325 130	1367 x 1326 x 850	2,18	200
H-P081VE6325 150	1367 x 1525 x 850	2,54	220

* - Picture above presents unit with either some or all available extras. Please note that the look of basic version of cabinet, or one of your choice, may vary from presented.

Refrigerated Pastry Cabinet - H-P081VE6325



H-P081VE6325*

Description:

- temperature range +2 / +5°C
- preferred ambient temperature +16 / +25°C
- power supply 230V / 50Hz
- internal condensing unit
- ecological polyurethane insulation
- body made of PVC coated steel - white
- bottom exposition shelf made of PVC coated steel - 'stainless steel' look
- black shelf frames
- 3 LED illuminated exposition shelves with height and angle adjustment
- LED top lighting
- openable (tilting) front glass with anti fog system
- back sliding doors
- forced air circulation
- electronic control with temperature display
- automatic defrost system
- automatic condensate evaporation
- 1 year full warranty service and after warranty service provided

Available options:

- multiplexing
- body made of PVC coated steel - black
- bottom exposition shelf made of stainless steel
- body made of PVC coated steel in RAL colours
- bottom exposition shelf made of PVC coated steel in RAL colours
- stainless steel shelf frames
- mirror in back sliding doors
- castors with brakes

* - Picture above presents unit with either some or all available extras. Please note that the look of basic version of cabinet, or one of your choice, may vary from presented.