


Catering Storage Freezers- I-Ola P M GASTRO



I-Ola P M Gastro*

Technical parameters:

Model	Dimension (ext.) H x W x D [mm]	Capacity [dm ³]	Shelves with low base	Power Consumption [kWh/24h]	Weight [kg]
I-Ola P M GASTRO	1980 x 1400 x 870	1400	11	9,50	200

* - Picture above presents unit with either some or all available extras. Please note that the look of basic version of cabinet, or one of your choice, may vary from presented.

Catering Storage Freezers- I-Ola P M GASTRO



I-Ola P M Gastro*


Description:

- temperature range -12 / -18°C
- preferred ambient temperature +16 / +25°C
- power supply 230V / 50Hz
- internal condensing unit
- ecological polyurethane insulation
- body made of powder coated steel in white colour
- interior made of stainless steel
- electronic control with digital temperature display
- self-closing door
- heated door frame
- 10 shelves (530x650mm)
- frame with rails prepared for GN1/1 trays
- forced air circulation with fan switch when doors are opened
- automatic defrost
- automatic condensate evaporation
- 1 year full warranty service and after warranty service provided

Available options:

- body made of powder coated steel - optional colours
- body made of stainless steel
- interior made of acid resistant stainless steel
- interior LED illumination
- additional shelf
- GN 1/1 tray 40mm deep
- GN 1/1 tray 100mm deep

Optional colours:



* - Picture above presents unit with either some or all available extras. Please note that the look of basic version of cabinet, or one of your choice, may vary from presented.